

Product Datasheet

705	
Main characteristics	<ul style="list-style-type: none"> * Fine definition with consistent release * Good abrasion and scratch resistance * Good adhesion properties on OPP laminates, printed unprinted and lacquered surfaces. * Applicable on all machine types in the graphics industry
Substrate	Plain paper and board, printed paper and board, embossed paper, coated paper, PVC labels, OPP film laminated paper, PP synthetic paper.
Recommend applications	Wine and spirit boxes, labels, cigarette packages, cosmetic packaging boxes, greeting cards other applications in graphics industry.
Relevant equipment	Vertical, Clam-shell ,Cylinder and Rotary machines
Operating hints	<ul style="list-style-type: none"> *Vertical, platen and clam-shell machines: 105°C - 135°C *Cylinder machines: 130°C - 160°C *Rotary machines: 200°C - 240 °C *Adjusting a higher speed or lower temperature to get the fine line definition *Ensure that the Die surface is clean. *Ensure that ink on the substrate (if any) is dry before stamping.
Availability	Gold/Matte Gold, Silver/Matte Silver and dark shades are available, please check color chart
Specification	Standard roll : 12μ × 640mm × 120m in 1"inch core Jumbo roll : 12μ × 1280mm × 3000M in 3"inch core Other roll formats are available to order - please enquire.
Order Instruction	MOQ for Gold/Silver : 200 standard rolls or Jumbo roll 12000M
Shelf life and storage	<ol style="list-style-type: none"> 1. Use Univacco product within one year after production 2. Keep product in its original package and away from high temperature, sunlight exposure and humidity. 3. Master rolls are best stored vertically. If store horizontally, please keep the original boxes and packages for your storage. 4. Jumbo rolls should be suspended horizontally and avoid direct contact with the ground or other items.
Issue Number	A.2
Date	2015/06/17

All UNIVACCO products have been developed for a particular range of applications. However, experience shows that substrates, printing equipment and operating conditions can vary, and users of our products are urged to verify, by means of test printing, that particular grades are appropriate for their specific applications. For this purpose, test samples are available on request. If you need help, UNIVACCO will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.